

## Factory Tough™ IP67 Industrial Camera



- Shock and vibration certified
- IP67 ready, PoE
- Lightweight, compact 29x29 mm
- Active sensor alignment



**IP67 Protection**  
with IP67 lens tube  
and IP67 cables



Polarization  
Models  
Available

### Triton Models

Model	MP	Resolution	FPS	Sensor	Format	Pixel Size	Shutter	Lens Mount	Chroma	GigE Interface
TRI245S	24.5 MP	5320 x 4600 px	4.5 fps	Sony IMX540 CMOS	4/3"	2.74 µm	Global	C	M/C	M12
TRI204S	20.4 MP	4510 x 4510 px	5.5 fps	Sony IMX541 CMOS	1.1"	2.74 µm	Global	C	M/C	M12
TRI200S	20.0 MP	5472 x 3648 px	5.6 fps	Sony IMX183 CMOS	1"	2.40 µm	Rolling	C	M/C	M12
TRI162S	16.2 MP	5320 x 3040 px	6.9 fps	Sony IMX542 CMOS	1.1"	2.74 µm	Global	C	M/C	M12
TRI124S	12.3 MP	4096 x 3000 px	9.0 fps	Sony IMX545 CMOS	1/1.1"	2.74 µm	Global	C	M/C	M12
TRI120S	12.3 MP	4096 x 3000 px	9.0 fps	Sony IMX304 CMOS	1.1"	3.45 µm	Global	C	M/C	M12
TRI122S	12.2 MP	4024 x 3036 px	9.1 fps	Sony IMX226 CMOS	1/1.7"	1.85 µm	Rolling	C	M/C	M12
TRI089S	8.9 MP	4096 x 2160 px	12.5 fps	Sony IMX267 CMOS	1"	3.45 µm	Global	C	M/C	M12
TRI081S	8.1 MP	2840 x 2840 px	13.8 fps	Sony IMX546 CMOS	2/3"	2.74 µm	Global	C	M/C	M12
TRI071S	7.1 MP	3208 x 2200 px	15.8 fps	Sony IMX428 CMOS	1.1"	4.5 µm	Global	C	M/C	M12
TRI064S	6.3 MP	3072 x 2048 px	17.7 fps	Sony IMX178 CMOS	1/1.8"	2.40 µm	Rolling	C	M/C	M12
TRI054S	5.4 MP	2880 x 1860 px	20.8 fps	Sony IMX490 CMOS	1/1.55"	3.0 µm	Rolling	C	Color HDR	M12
TDR054S	5.4 MP	2880 x 1860 px	13.8 fps	Sony IMX490 CMOS	1/1.55"	3.0 µm	Rolling	C	Color (AltaView On-Camera Adaptive Tone Mapping)	M12
TRI050S-P/Q	5.0 MP	2448 x 2048 px	22 fps	Sony IMX250MZR CMOS Sony IMX250MYR CMOS	2/3"	3.45 µm	Global	C	Polarized M Polarized C	M12
TRI050S1-P/Q	5.0 MP	2448 x 2048 px	22 fps	Sony IMX264MZR CMOS Sony IMX264MYR CMOS	2/3"	3.45 µm	Global	C	Polarized M Polarized C	M12
TRI051S	5.0 MP	2448 x 2048 px	22 fps	Sony IMX547 CMOS	1/1.8"	2.74 µm	Global	C	M/C	M12
TRI050S	5.0 MP	2448 x 2048 px	22 fps	Sony IMX264 CMOS	2/3"	3.45 µm	Global	C	M/C	M12
TRI032S	3.2 MP	2048 x 1536 px	35.4 fps	Sony IMX265 CMOS	1/1.8"	3.45 µm	Global	C	M/C	M12
TRI028S	2.8 MP	1936 x 1464 px	39.2 fps	Sony IMX429 CMOS	2.3"	4.5 µm	Global	C	M/C	M12
TRI023S	2.3 MP	1920 x 1200 px	48.3 fps	Sony IMX392 CMOS	1/2.3"	3.45 µm	Global	C	M/C	M12
TRI016S	1.6 MP	1440 x 1080 px	71.6 fps	Sony IMX273 CMOS	1/2.9"	3.45 µm	Global	C	M/C	M12
TRI005S	0.5 MP	812 x 620 px	166.4 fps	Sony IMX433 CMOS	1/1.7"	9.0 µm	Global	C	M/C	M12
TRI004S	0.4 MP	720 x 540 px	286 fps	Sony IMX287 CMOS	1/2.9"	6.9 µm	Global	C	M/C	M12



### SMART Triton SMART Model – Intelligent Vision with Ai Processing

Model	MP	Resolution	FPS	Sensor	Format	Pixel Size	Shutter	Lens Mount	Chroma	Interface
TRSI23S-CC	12.3 MP	4056 x 3040 px	7.9 fps	Sony IMX501 CMOS	1/2.3"	1.55 µm	Rolling	C	Color	M12

## Specifications

Interface, Power, and Size Information	
Digital Interface	1000BASE-T GigE M12, PoE
GPIO Interface	8 pin M8 connector
Opto-isolated I/O ports	1 input, 1 output
Non-isolated I/O ports	2 bi-directional
Dimensions	29 x 29 x 45* mm
Lens Mount	C-mount
Weight	67 g
Power Requirement	PoE (IEEE 802.3af), or 12-24 VDC external
Power Consumption	2.5W via V_ext; ~3.1W via PoE

\*Not including lens barrel or interface ports

Standard and Certifications	
Standard	GigE Vision v2.0
Compliance	CE, KC, FCC, BIS, RoHS, REACH, WEEE
Ingress Protection	IP67 (For IP67 protection Triton must be used with IP67 lens tube and cables)
Storage Temperature	-30 to 60°C
Operating Temperature	-20 to 55°C ambient
Shock and Vibration	DIN EN 60068-2-27, DIN EN 60068-2-64 DIN EN 60068-2-6
Humidity	Operating: 20% ~ 80%, relative, non-condensing
Warranty	3 year

Imaging Properties	
Image Buffer	128 MB
Image Processing	Gain, gamma, black level, white balance, LUT, CCM, pixel correction, hue, saturation, color space conversion
Pixel Formats	Mono8/10/12/16, Bayer8/10/12/16, RGB8, YUV422, YUV411Mono8/12/16, PolarizeMono8/12/16 (TRIO50S-P) BayerRG8/12/16, PolarizeMono8/12/16 (TRIO50S-Q)
Image Modes	Horizontal and vertical binning, decimation, ROI, horizontal and vertical flip
ADC	12 bit
Gain Range	0 dB to 48 dB analog and digital
Exposure Time	47.2 μs to 10 s <b>**varies by model, see our website</b>

Camera Features	
User Sets	1 default and 2 custom user set
File system size	16 MB
Chunk Data	Frame counter, offset X/Y, width/height, exposure time, gain, black level, line status, sequencer set
Event Data	Acquisition start/end, exposure start/end, line rise/fall, error
Counter & Timer	2 counters and 2 timers
Sequencer	Exposure time, gain
Synchronization	Software trigger, hardware trigger, PTP (IEEE 1588)

### C-Mount Model

